

| Item | Vturn-A16 | Vturn-A20 | VT-A26 |
|---------------------------|---|------------------|---------------|
| Extend model (Bed Length) | | | 85/130 |
| Available options | Big bore, Live turret, Y-axis, Sub-spindle | | |
| Swing Over bed | 27.56 | 27.56 | 35.43 |
| Max Turning Dia. | 15.35 | 15.35 | 16.54 |
| Swing Over Carriage | 21.65 | 21.65 | 27.56 |
| Max.Travel + X dir | 7.68 | 7.68 | 8.27 |
| - X dir | 0.98 | 0.98 | 1.97 |
| Max. Travel (Z-axis) | 23.62 | 23.62 | 33/51 |
| Center Distance | 24.8 | 24.8 | 35/53 |
| Rapid -X axis (ipm) | 945 | 945 | 945 |
| Z axis (ipm) | 945 | 945 | 945 |
| | | | |
| Spindle Motor H.P | 15/25 | 15/20 | 30/30 |
| Hyd. Power Chuck | 6 | 8 | 10 |
| Spindle Speed | 6000 | 5000 | 4500 |
| Spindle Nose | A2-5 | A2-6 | A2-8 |
| Hole Thru Spindle | 2 | 2.44 | 3.39 |
| Hole Thru Chuck Tube | 1.57 | 2 | 2.95 |
| Spindle Bearing Dia. | 3.54 | 3.94 | 5.12 |
| Spindle Taper | 1/20 | 1/20 | 1/20 |
| | | | |
| X-Z Way's | BOX | BOX | BOX |
| Turret Tool Stations | 12 | 12 | 12 |
| O.D. Tool Size | 3/4" | 3/4" | 1 |
| I.D. Tool Size | 1-1/4" | 1-1/4" | 2 |
| Turret Index Time | 1.05/1.44 | 1.05/1.44 | 1.05/1.44 |
| | | | |
| X Feed motor H.P. | 4 | 4 | 4 |
| Z Feed motor H.P. | 4 | 4 | 5.5 |
| | | | |
| Tail Stock Quill Dia. | 2.95 | 2.95 | 4.33 |
| Tail Stock Quill Stroke | 3.15 | 3.15 | 3.94 |
| Tail Stock Quill Taper | MT-4 | MT-4 | MT-5 |
| | | | |
| Coolant Capacity (Gal) | 76 | 76 | 95/108 |
| Machine Size L | 172 | 172 | 190/217 |
| W | 69 | 69 | 83 |
| Weight lbs | 12,540 | 12,760 | 16,720/19,800 |